

FULL CINEFADE KIT LIST



cmotion Cinefade VariIND - Motorised Polariser
The motorised filter tray holds one of the two custom ARRI circular polarisers and is connected via an LBUS cable to either a cPRO motor, cPRO camin or directly to a power source.



cmotion Cinefade VariIND - Static Polariser
The static filter tray holds the second custom ARRI circular polariser and can be fixed to the Motorised Polariser to be placed into a matte box together.



cmotion cPRO motor
The kit includes one cPRO motor, with a built-in rf module, antenna, bracket and 0.8 gear that should be used for focus or iris control.



ARRI cforce mini motor (optional)
The kit includes one cforce mini motor, bracket, 0.8 gear and attached cable that can be used for focus control or ideally for iris control.



cmotion cPRO hand unit
The cPRO hand unit has a focus knob, iris slider, zoom joystick and VariIND thumbwheel, as well as a touchscreen to navigate the menu. An antenna, plain focus marker ring and plain iris strip are included.



cPRO camin (optional)

The camin is a wireless motor box and can be mounted on the camera to remotely control the VariIND and RotaPola or a motor. Antenna is included.



Mounting bracket (optional)

Quick release mounting bracket with one 3/8" and two 1/4" screws. Allen Key 2.5mm included



LBUS to LBUS cable

LBUS (4p/m) to LBUS (4p/m) cables in different lengths (0.2m, 0.3, 0.5m, 0.8m).



LBUS to LBUS cable (angled)

LBUS (4p/m/angled) to LBUS (4p/m/straight) cables two lengths (0.35, 0.8m).



LBUS to RS Power

LBUS (4p/m) to RS (Fi 3p/m) in 0.8m length.



LBUS to D-tap Power

LBUS (4p/m) to D-tap (Anton Bauer 2p) cable in 0.8m length.



CAM to LBUS cable

CAM (7p/m) to LBUS (4p/m) cable in 0.5m length.



CAM to CAM cable

CAM (7p/m) to LBUS (7p/f) cable in 0.3m length.



CAM to RS Power

CAM (7p/m) to RS (Fi 3p/m) cable in 0.3m length.



CAM to D-tap

CAM (7p/m) to D-tap (Anton Bauer 2p) cable in 0.5m length.



Batteries

Two cmotion cPRO Lithium-ion batteries are supplied.



Charger and cable

One dual-charger, cable and EU plug are supplied.



Power adapter

A universal travel adapter for local power sockets.



Strap

The strap can be attached to the cPRO hand unit.



Belt clip

Spider black widow belt clip for cPRO hand unit.



Extra motor gears (optional)

A 25mm wide gear (m0.8 40t) for moving lens barrels and a gear for Panavision lenses (m0.4 80t)



User manual

A hard copy is provided with each kit. A digital version is available at www.cinefade.com/manual



Pelicase

The Pelicase 1510 has a custom foam insert that fits the entire kit inside a carry-on sized case with wheels. Dimensions (mm) 559 (L) x 351 (W) x 229 (D).